

Ham 91B - ASV Maker - Register
Dr. Marc & Rosemary © 2300206

- AllStar is an amateur radio system which allows connecting radios, repeaters, and computers to create a network accessible around the world.
- USER ID: Because so many systems and items interconnect, the user needs to have multiple accounts:
 - FCC Ham License, AllStarLink.org website, AllStarLink nodes, Raspberry Pi hostname, Iax Pc access.
 - Record your email address, user ID, a password for each, and a number associated with each.
 - Different callsigns are allowed for each node.
 - Write them down.
- CREATE AN ACCOUNT: Go to <https://AllStarLink.org>.
 - Click <Sign Up>. It may take a few hours to get confirmed.
- ONCE YOU HAVE AN ACCOUNT: Request two node numbers.
 - Login.
 - Go to > Portal > Servers. Give the first server a name to remember.
 - Give the second server a name.
 - Go to > Portal > Nodes.
 - Associate each node number with a server. Each can have a different password.
 - CAUTION PASSWORDS: No special characters allowed by HamVoip yet.
- SUGGESTION:
 - Let the first node (ends in 0) be simply your callsign (KI5xxx).
Use this with your cellphone.
 - Make the second node a link, your callsign-L (KI5xxx-L).
Use this with your Raspberry Pi.
 - This arrangement allows you to use your cellphone to test your node.
- NEXT VISITS: You will come back to this screen several times.
 - After you construct the node with a Raspberry Pi, come here to check if you are connected.
 - Registered = yes, means ASL sees your node running.
- OPERATION: Fortunately, operation is very simple.
 - You only need the phone number (node number).
 - It is just a phone system at this point.
 - DTMF keypad, like a phone, calls and controls the station.
- Life is good. Enjoy!

